

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/053361 A1

(51) International Patent Classification⁷: **F16H 61/00**

(21) International Application Number:
PCT/NL2003/000878

(22) International Filing Date:
10 December 2003 (10.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1022157 12 December 2002 (12.12.2002) NL

(71) Applicant (for all designated States except US): **VAN DOORNE'S TRANSMISSIE B.V.** [NL/NL]; Patent Department (AE-CT/EL-P), Postbus 500, NL-5000 AM Tilburg (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **VAN DER LEEST,**

Adrianus, Johannes, Wilhelmus [NL/NL]; Vezelstraat 12, NL-5388 RX Nistelrode (NL). **VAN SPIJK, Johannes, Gerardus, Ludovicus, Maria** [NL/NL]; Grotestraat 253, NL-5151 BM Drunen (NL).


(74) Agent: **VAN DOORNE'S TRANSMISSIE B.V.**; Att. Plevier, Gabriël, Anton, Johan, Maria, Manager Patent Department (AE-CT/EL-P), Postbus 500, NL-5000 AM Tilburg (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **CONTINUOUSLY VARIABLE TRANSMISSION**



(57) Abstract: Continuously variable transmission (1) for motor vehicles, provided with a primary pulley (2) and a secondary pulley (3), around which a drive belt (10) is arranged, clamped between two conical pulley discs (21, 22; 31, 32) of the respective pulley (2; 3), a running surface of at least one pulley disc (21; 22; 31; 32) of the primary pulley (2) and the secondary pulley (3), by means of which running surface this pulley disc is in contact with the drive belt (10), being provided, as seen in a cross section oriented perpendicular to a tangential direction, with a curvature, so that a pulley angle between a tangent on the running surface and a radial direction varies between a lowest value at the location of a radially innermost position on the running surface and a highest value at the location of a radially outermost position on the running surface, in which transmission the curvature of the running surface of the primary pulley (2) and the curvature of the running surface of the secondary pulley (3) differ from one another.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

CONTINUOUSLY VARIABLE TRANSMISSION

The present invention relates to a continuously variable transmission in accordance with the preamble of Claim 1 for transmitting mechanical power between
5 an engine and a load, it being possible for the transmission ratio of the torque level and the rotational speed between the pulleys to be varied continuously within a set range. Transmissions of this type are generally known and are suitable in particular for use in motor vehicles.

As is known, in the transmission the drive belt is clamped between two conical
10 pulley discs of the respective pulleys, the ratio of the radial position of the drive belt in the primary and secondary pulleys, which is also known as the primary and secondary running radii, determining the transmission ratio of the transmission. The size of the abovementioned running radii can be varied in opposite directions by virtue of the fact that one of the pulley discs of each pulley is arranged in such a manner that it can be
15 moved in the axial direction. In the transmission ratio equal to one, the abovementioned running radii of the drive belt are therefore equal to one another, while at a transmission ratio of greater than one the primary running radius is greater than the secondary running radius, and vice versa.

It is known, inter alia from EP-A-0291129, that while the transmission ratio is
20 being varied, the centre of the drive belt, i.e. a position halfway along the axial distance between the pulley discs, shifts in a manner which differs for each pulley. Consequently, the drive belt between the pulleys will, in virtually all possible transmission ratios, not be oriented perpendicular to the pulley axle, i.e. the axial direction, but rather at a small and varying angle with respect thereto. This
25 phenomenon is referred to as the skew running of the drive belt. It is recognized that skew running of the drive belt may have adverse effects on the functioning of the transmission, for example in terms of increased noise production or uneven wear. As a solution to this phenomenon, it is proposed, inter alia in Japanese Patent Application 63-053352, but also, for example, in JP-2002-031215, for the running surface of at
30 least one pulley disc of each pulley, i.e. the contact surface of this disc with the drive belt, as seen in a cross section oriented perpendicular to the tangential direction, to be provided with a curvature. By suitable selection of the said curvature, it is possible to ensure that the drive belt always, i.e. irrespective of the instantaneous transmission ratio of the transmission, advantageously remains oriented substantially perpendicular
35 to the pulley axles.

In some cases, it is also possible to select to partially compensate for the skew running by reducing at least the maximum angle of the drive belt with respect to the axial direction. Moreover, as well as the compensation for skew running, the literature also discloses other phenomena for which the use of running surfaces which are curved to a prescribed extent may be advantageous. In each case, an angle between a tangent on the respective contact surface and a radial direction, which angle is referred to here as the pulley angle, runs from a lowest value at the location of a radially innermost position on the contact surface to a highest value at the location of a radially outermost position on the contact surface.

Although the known transmission fundamentally functions correctly, according to the invention it is still worthy of improvement. In particular, the invention relates to a reduction in the mechanical load on the drive belt during operation of the transmission, in such a manner that its service life and/or maximum load-bearing capacity is improved.

To this end, the transmission according to the invention is characterized in accordance with Claim 1. Surprisingly, in a transmission of this type, the forces which occur between drive belt and pulleys during operation of the transmission are taken into account. The invention is based on the principle that an axially oriented clamping force exerted on the drive belt by the pulley discs for the purpose of torque transmission exerts a radially oriented force component on the drive belt on account of the pulley angle between the pulley disc and drive belt. On account of the fact that this force component is exerted on the two pulleys, the radial position or running radius of the drive belt can remain constant, but at the expense of a tensile force in the drive belt. This tensile force applies a mechanical load to the drive belt, which is in principle undesirable, since this load makes little or no contribution to the transmission of torque between the pulleys. The abovementioned force component and the tensile force in the drive belt resulting therefrom increase as the pulley angle becomes greater. In view of this aspect, it may therefore be deemed advantageous to use the smallest possible pulley angle.

However, a small pulley angle has the significant drawback that in the event of a given deformation of the pulley discs, also known as the expansion of the pulley discs, as occurs during operation under the influence of the clamping force, the drive belt coils inward to some extent in the radial direction between the pulley discs, away from the ideal arcuate path contour. The extent to which this effect occurs is referred to as the radial sag of the drive belt. When this occurs, parts of the drive belt slip with

respect to the pulley discs, such that the efficiency of the transmission is adversely affected, which is fundamentally undesirable. Geometric considerations mean that the abovementioned radial sag and the resulting loss of efficiency increase as the pulley angle becomes smaller, as the running radius of the drive belt becomes greater or as
5 the clamping force increases. In view of this aspect, it may therefore be deemed advantageous to use the largest possible pulley angle, certainly at a relatively high running radius.

The invention combines the abovementioned fundamentally contradictory effects in a surprising way, such that the service life and/or robustness of the known
10 transmission is enhanced while its efficiency is not or is scarcely adversely affected. To this end, the invention is partly based on the characteristic feature which arises as a result of the transmission being used in motor vehicles, whereby, during operation, in the lowest transmission ratio - as defined in accordance with the present invention - it is subject to a relatively heavy but brief load, whereas in the highest transmission ratio
15 it is subject to a less heavy load but for a prolonged period of time. The lowest transmission ratio is used when a load, i.e. the motor vehicle, is being accelerated, for example from a stationary position, while the highest transmission ratio is used, for example, after the load has reached a desired, more or less constant speed.

According to the invention, therefore, it can be concluded that it is advantageous
20 if, in the lowest transmission ratio, contact between the pulleys and the drive belt, both on the primary pulley and on the secondary pulley, takes place at relatively low pulley angles, in order to minimize the abovementioned tensile force, and if, in the highest transmission ratio, the opposite applies, in order to minimize the abovementioned radial sag. Although the abovementioned curvature of the running surface of the
25 primary pulley does comply with an advantageous profile of the pulley angle of this nature, according to the invention this is not the case for the secondary pulley. According to the invention, it is advantageous if the highest value for the pulley angle of the secondary pulley is lower than that of the primary pulley. After all, it is this pulley angle which determines the contact between the drive belt and the secondary pulley in
30 the lowest transmission ratio, in which the tensile force effect prevails over the radial sag effect.

In order to leave the range in which the pulley angle of the secondary pulley varies, i.e. the difference between the highest and lowest values for this angle, unchanged, the lowest value for the pulley angle, at a small running radius, should be
35 correspondingly lower. The expectation could be that this would have a

correspondingly adverse effect on the efficiency of the transmission in the highest transmission ratio. According to the invention, however, a disadvantageous effect of this nature does not occur or scarcely occurs, since, as has already been noted, the radial sag decreases proportionally to the decreasing running radius, in an initial
5 approximation even to the power of three. Near to the smallest running radius, therefore, little or no radial sag occurs.

Nevertheless, according to the invention in a preferred embodiment of the transmission it may be advantageous for the lowest value of the pulley angle of the secondary pulley not to be correspondingly lower, so that the range of the pulley angle
10 for the secondary pulley is smaller than the range for the primary pulley. This is because a lower limit for the value of the pulley angle is generally necessary in order to realize a radially oriented clamping force component of sufficient magnitude to enable the friction between pulley and drive belt in the radial direction to be overcome, so that the transmission ratio of the transmission can be varied. In addition, in the case
15 of a drive belt designed as what is known as a push belt with at least one continuous flexible ring, over the periphery of which a series of transverse elements, which can move freely over the ring at least in its longitudinal direction, is arranged, sufficient tensile force has to be realized in the ring to enable the torque supplied to be transmitted between the pulleys by means of pushing forces between the transverse
20 elements. This aspect is described in European Patent Publication EP-A 0 931 959. In a particular embodiment of the transmission, the lowest value for the pulley angle of both pulleys is equal, for the above reasons.

To maintain the effect which it is desired to achieve with a curvature of the contact surface in accordance with the prior art, in which the primary and secondary
25 curvature are equal, despite the narrower range of the pulley angle of the secondary pulley, in practice it will often be desirable to increase the range of the pulley angle of the primary pulley accordingly, for example by reducing its lowest value or increasing its highest value. In the former case, according to the invention the efficiency of the transmission will not or will scarcely be adversely affected, since, as has already been
30 indicated above, the discs will scarcely expand in the vicinity of the lowest running radius. In the latter case, according to the invention it is even possible to expect an improved action of the transmission, since the radial sag advantageously decreases in the highest transmission ratio.

The invention is explained in more detail below with reference to the figures and
35 the exemplary embodiments illustrated therein.

Figure 1 shows a diagrammatic cross section through a continuously variable transmission of the known type.

Figure 2 shows a pulley disc of the known transmission, and in particular its contact surface, in detail.

5 Figure 3 shows a simplified side view of the transmission shown in Figure 1.

Figure 4 shows a graph plotting the pulley angle as a function of the running radius of the drive belt for a primary pulley and a secondary pulley in accordance with the prior art.

10 Figure 5 shows a graph corresponding to Figure 4 in which the pulley angles are determined in accordance with a possible embodiment of the invention.

Figure 1 diagrammatically depicts a cross section through the known continuously variable transmission 1. The transmission 1 comprises a primary pulley 2 which can be driven by an engine (not shown) and a secondary pulley 3 which drives a load (not shown), both of which pulleys are provided with a pulley disc 21, 31 which is
15 fixed to the respective pulley axle 20, 30 and with a pulley disc 22, 32 which can be displaced in the axial direction with respect to the said axle 20, 30. A drive belt 10 is clamped between the pulley discs 21, 22, 31, 32, so that mechanical power can be transmitted between the two axles 20 and 30 with the aid of friction. The transmission ratio of the transmission 1 is in this case determined by the ratio of a primary running
20 radius R_p and a secondary running radius R_s of the drive belt 10, i.e. its effective radial position between the pulley discs 21, 22, 31, 32 of the respective pulleys 10 and 20. The running radii R_p and R_s and therefore the transmission ratio R_p/R_s of the transmission 1 can be varied by causing the displaceable discs 22, 32 to move in opposite axial directions along the respective pulley axles 20, 30. In the figure, the
25 transmission 1 is illustrated by way of example with a high transmission ratio, i.e. with a relatively large primary running radius R_p and a relatively small secondary running radius R_s .

Figure 2 shows a more detailed illustration of an arbitrary pulley disc 43 on the basis of a cross section seen in the tangential direction. The running surface 40 or
30 contact surface 40 of the pulley disc 43 is provided with a curvature, with a pulley angle α , defined between a tangent 41 at a point R on the contact surface 40 and a radial direction 42, increasing as seen in this radial direction.

Figure 3 shows a side view of the known transmission 1, with the primary pulley 2 with the primary axle 20 on the left-hand side of the figure and the secondary pulley
35 3 with the secondary axle 30 on the right-hand side of the figure. The lines L, M and H

indicate the position of the drive belt 10 in three transmission ratios of the transmission. The dashed line L indicates the lowest transmission ratio, in which the transmission 1, during normal operation, is subject to a relatively short but heavy load, for example when the load, i.e. the motor vehicle, is being accelerated from a stationary position. The dot-dashed line H indicates the highest transmission ratio, in which the transmission 1, during normal operation, is subject to a relatively prolonged less heavy load, for example after the motor vehicle has reached a desired speed. The dot-dashed line M indicates, as an additional example, the transmission ratio equal to 1, in which the primary running radius R_p is equal to the secondary running radius R_s and the primary axle 20 and the secondary axle 30 have the same rotational speed.

Figure 4 shows a graph which plots the pulley angle α —defined in accordance with Figure 2 - of the primary pulley 2 and of the secondary pulley 3 in relation to the respective running radius R_p , R_s of the drive belt 10. In this example, the pulley angles in relation to the running radius $\alpha(R_p)$, $\alpha(R_s)$ are given by the known requirement that the drive belt 10, in all possible transmission ratios R_p/R_s be oriented substantially perpendicular to the pulley axes 20 and 30. For both pulleys 2, 3 the pulley angle α varies between approximately 7.5° and 10.8° .

Figure 5 illustrates a similar graph, plotting the pulley angles in relation to the respective running radius $\alpha(R_p)$, $\alpha(R_s)$, but in accordance with a possible embodiment of the invention. According to the invention, the highest value for the pulley angle of the secondary pulley ($\pm 8.8^\circ$) is advantageously smaller than that of the primary pulley ($\pm 11^\circ$), while the respective lowest values therefor ($\pm 7^\circ$) approximately correspond to one another. Compared to the graph shown in Figure 4, in the transmission according to the invention the range for the pulley angle α for the secondary pulley 3 has become smaller. Nevertheless, the transmission according to the invention can also substantially comply with the requirement given above.

In addition to what has been described above, the invention also relates to all the details shown in the figures, at least to the extent that they are directly and unambiguously recognizable to a person skilled in the art, and to the features described in the set of claims which follows.

CLAIMS

1. Continuously variable transmission (1) for motor vehicles, provided with a primary pulley (2) and a secondary pulley (3), around which a drive belt (10) is arranged, clamped between two conical pulley discs (21, 22; 31, 32) of the respective pulley (2; 3), a running surface (40) of at least one pulley disc (44) of the primary pulley (2) and the secondary pulley (3), by means of which running surface this pulley disc is in contact with the drive belt (10), being provided, as seen in a cross section oriented perpendicular to a tangential direction, with a curvature, so that a pulley angle (α) between a tangent (41) on the running surface (40) and a radial direction (42) varies between a lowest value at the location of a radially innermost position on the running surface (40) and a highest value at the location of a radially outermost position on the running surface (40), characterized in that the curvature of the running surface (40) of the primary pulley (2) and the curvature of the running surface (40) of the secondary pulley (3) differ from one another.
2. Transmission (1) according to Claim 1, characterized in that the highest value for the pulley angle (α) of the secondary pulley (3) is lower than the highest value for the pulley angle (α) of the primary pulley (2).
3. Transmission (1) according to Claim 1 or 2, characterized in that a range between the highest value and the lowest value for the pulley angle (α) of the secondary pulley (3) is smaller than a corresponding range of the pulley angle (α) of the primary pulley (2).
4. Transmission (1) according to Claim 1, 2 or 3, characterized in that the lowest value for the pulley angle (α) of the secondary pulley (3) is equal to the lowest value for the pulley angle (α) of the primary pulley (2).
5. Motor vehicle having an engine and a load which is to be driven, between which a transmission (1) according to one of the preceding claims is incorporated, a power which is to be generated by the engine being transmitted by the drive belt (10) from the primary pulley (2) to the secondary pulley (3) and being released to the load by the secondary pulley (3).




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No.

P/NL 03/00878

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16H61/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F16H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 04, 30 April 1997 (1997-04-30) & JP 08 326859 A (SUZUKI MOTOR CORP), 10 December 1996 (1996-12-10) abstract; figures 1,4	1, 3, 4
X	US 5 328 412 A (DURUM METIN M) 12 July 1994 (1994-07-12) claim 1	1
A	PATENT ABSTRACTS OF JAPAN vol. 2002, no. 05, 3 May 2002 (2002-05-03) & JP 2002 031215 A (NISSAN MOTOR CO LTD), 31 January 2002 (2002-01-31) cited in the application abstract	1
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

16 March 2004

Date of mailing of the international search report

23/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Goeman, F

INTERNATIONAL SEARCH REPORT

Internatic
NL 03/00878

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 013, no. 183 (M-820), 28 April 1989 (1989-04-28) & JP 01 012167 A (TOYOTA AUTOM LOOM WORKS LTD), 17 January 1989 (1989-01-17) abstract; figures ----	1
A	PATENT ABSTRACTS OF JAPAN vol. 012, no. 272 (M-724), 28 July 1988 (1988-07-28) & JP 63 053352 A (FUJI HEAVY IND LTD), 7 March 1988 (1988-03-07) cited in the application abstract; figure 2 ----	1
A	US 4 631 042 A (RATTUNDE MANFRED) 23 December 1986 (1986-12-23) figures ----	1
A	EP 1 158 210 A (DOORNES TRANSMISSIE BV) 28 November 2001 (2001-11-28) abstract ----	1
A	US 6 206 796 B1 (LEE JONG-WAN) 27 March 2001 (2001-03-27) claim 1 -----	1

INTERNATIONAL SEARCH REPORT

Internati Application No
P NL 03/00878

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 08326859	A	10-12-1996	NONE	
US 5328412	A	12-07-1994	NONE	
JP 2002031215	A	31-01-2002	NONE	
JP 01012167 5	A	12-05-1998	NONE	
JP 63053352 5	A		NONE	
US 4631042	A	23-12-1986	DE 3447092 A1 FR 2575258 A1 GB 2169043 A ,B IT 1183001 B JP 61157862 A	03-07-1986 27-06-1986 02-07-1986 05-10-1987 17-07-1986
EP 1158210	A	28-11-2001	EP 1158210 A1 WO 0192763 A1 EP 1299659 A1 JP 2003535289 T US 2003144097 A1	28-11-2001 06-12-2001 09-04-2003 25-11-2003 31-07-2003
US 6206796	B1	27-03-2001	KR 2000008819 A BR 9902829 A CA 2277388 A1 DE 19934047 A1 ES 2164541 A1 FR 2781855 A1 GB 2339867 A ,B ID 23620 A IT MI991585 A1 JP 2000120817 A	15-02-2000 15-02-2000 16-01-2000 27-01-2000 16-02-2002 04-02-2000 09-02-2000 04-05-2000 16-01-2001 28-04-2000

CLAIMS

1. Continuously variable transmission (1) for motor vehicles, provided with a primary pulley (2) and a secondary pulley (3), around which a drive belt (10) is arranged, clamped between two conical pulley discs (21, 22; 31, 32) of the respective pulley (2; 3), a running surface (40) of at least one pulley disc (44) of the primary pulley (2) and the secondary pulley (3), by means of which running surface this pulley disc is in contact with the drive belt (10), being provided, as seen in a cross section oriented perpendicular to a tangential direction, with a curvature, so that a pulley angle (α) between a tangent (41) on the running surface (40) and a radial direction (42) varies between a lowest value at the location of a radially innermost position on the running surface (40) and a highest value at the location of a radially outermost position on the running surface (40), characterized in that the curvature of the running surface (40) of the primary pulley (2) and the curvature of the running surface (40) of the secondary pulley (3) differ from one another by the feature that the highest value for the pulley angle (α) of the secondary pulley (3) is lower than the highest value for the pulley angle (α) of the primary pulley (2).
2. Transmission (1) according to Claim 1, characterized in that a range between the highest value and the lowest value for the pulley angle (α) of the secondary pulley (3) is smaller than a corresponding range of the pulley angle (α) of the primary pulley (2).
3. Transmission (1) according to Claim 1 or 2, characterized in that the lowest value for the pulley angle (α) of the secondary pulley (3) is equal to the lowest value for the pulley angle (α) of the primary pulley (2).
4. Motor vehicle having an engine and a load which is to be driven, between which a transmission (1) according to one of the preceding claims is incorporated, a power which is to be generated by the engine being transmitted by the drive belt (10) from the primary pulley (2) to the secondary pulley (3) and being released to the load by the secondary pulley (3).